


Nitrogen Advantage

PORTABLE NITROGEN INFLATION SYSTEM MODEL NA6-3P



Champion model number NA6-3P is the ideal solution for passenger and light truck facilities which need to be able to bring the generator and purge system to the vehicle instead of the vehicle to the system. This new portable system offers 3.2 scfm of nitrogen output and an automatic purge system that allows you to purge and inflate four tires at once! With an easy to read control panel, four quick-disconnect hoses and a balanced package for uneven floors, the Champion NA6-3P is the package you need.

STANDARD FEATURES

- ▶ 30 Gallon Receiver
- ▶ Four 25' Inflation Hoses
- ▶ Nitrogen Purity Port
- ▶ Pre-filters
- ▶ Hand-held Nitrogen Analyzer
- ▶ Air Products Prism™ Membrane
- ▶ Six Auxilliary Ports

OPTIONS

- ▶ Promotional Advertising Materials Kit
- ▶ Valve Stem Caps
- ▶ Kiosk Units
- ▶ Additional Hose for Auxilliary Ports



CHAMPION®

A Gardner Denver Product

Always be one.

PORTABLE NITROGEN INFLATION SYSTEM

| Feature | Details |
|------------------------------|-----------------------------|
| Air Input | 6.3 SCFM @ 125 psi @ 75° F |
| Air Input Range | 100–175 PSI |
| N2 Output | 3.2 SCFM @ 125 psi @ 75° F |
| N2 Purity | 95–99.9 % Purity |
| N2 Dewpoint | -70°F |
| Operating Temperature | 40° to 140° F |
| Inlet Port | 3/8" NPT |
| N2 Purity Port | Yes |
| Auto Shut Off | Yes |
| Pre-Filters | Two |
| Filter Maintenance Indicator | Yes |
| Air Inlet Pressure Gauge | Yes |
| N2 Outlet Pressure Gauge | Yes |
| Dimensions | 33" x 27" x 46" |
| Weight | 265 Lbs |
| Inflation Hoses | Four 25' Hoses Included |
| Aux. N2 Outlet Port | Yes |
| N2 Storage Tank | 30 Gallon |
| Inflator ByPass Port | 3/8" NPT |
| N2 Purges | 0–9 |
| Power Supply | (Rechargeable) 12V DC Ni-MH |
| Inflator Accuracy | +/- 0.3 psi |

NITROGEN OUTPUT

| 95% Purity | 98% Purity |
|--------------------|--------------------|
| 2.3 scfm @ 100 psi | 1.3 scfm @ 100 psi |
| 3.2 scfm @ 125 psi | 1.7 scfm @ 125 psi |
| 4.0 scfm @ 150 psi | 2.2 scfm @ 150 psi |
| 4.8 scfm @ 175 psi | 2.6 scfm @ 175 psi |



1301 North Euclid Avenue
 Princeton, Illinois 61356 USA
 Phone 888/436-5499
 Fax 815/872-0421
 E-mail: Champion@championpneumatic.com
www.ChampionPneumatic.com

